

connecting the future



TMS 5x16P - Stand alone 4SAT+1TER+PSU / 16out

Article number: 300327

Product description:

TRIAX TMS 5x Multiswitches - 4 polarities (1 positions + 1 ter.) For one satellite positions in smaller networks the TRIAX TMS 5XP series with build in power supply is the right choice.

Specifications

ORDER INFORMATION	
EAN Number	5702663003279
CHARACTERISTICS	
Max. output level SAT @ -35 dB IMD3	100 dB μ V
Max. output level TER @ -60dB IMD3	85 dB μ V
Switch commands	13/18 V, 0/22 kHz
FREQUENCY	
Frequency range TER	47-862 MHz
Frequency range SAT	950-2150 MHz
GAIN	

Gain - TER	4.0 dB
ISOLATION	
Isolation SAT to TER	22 dB
Isolation TER to SAT	22 dB
Isolation cross polarisation H/V	25 dB
Isolation out-out SAT	35 dB
Isolation out-out TER	28 dB
RETURN LOSS	
Return loss SAT inputs	10 dB
Return loss SAT outputs	8 dB
Return loss TER inputs	10 dB
Return loss TER outputs	8 dB
ELECTRICAL	
Impedance	75 Ω
OPERATIONAL	
Max. current pass per F-connector	600 mA
Temperature range	-20...+55 °C
CONNECTORS	
Connector Type	F-female
Number of inputs	5
Number of trunk inputs	4 SAT, 1 TER
Subscriber outputs	16
Colour coding of IF and TER inputs	VL=Black, VH=Red, HL=Green, HH=Yellow
MECHANICAL	
Main material	Steel housing
Product Height	71 mm
Product Depth	103 mm
Product Width	559 mm
Packing QTY	1
Packaging Height	0,550 m

Packaging Width	1,200 m
Packaging Depth	5,500 m
Packaging Volume	3,630 m ³
Net Weight	0,570 kg
Tara Weight	0,200 kg
Total Weight	0,770 kg
