



TECHNISTAR S6 Int. Edt.

HDTV digital satellite receiver with USB-PVR function

EAN	Colour	Item no.	Weight (Box)	Weight	Device (W x H x D)	Box
4019588647176	black	0006/4717	1.24 kg	600 g	22.00 x 4.50 x 17.70 cm	31.00 x 8.00 x 19.50 cm

TOP FEATURES

HDTV tuner (DVB-S/S2)

DVRready: Digital video recorder function for recording to USB hard drive

Timeshift in connection with USB hard drive

Operation on 12V

Multimedia streaming on home network (via UPnP, server)

Electronic program guide (EPG)

MULTIMEDIA

DVR function : Ja

DVR storage medium : via USB

Timeshift : Yes

Recordings edition function : Yes

Recordings folder management : Yes

Smartcard reader : Yes

Digital electric audio output : Yes

audio/video output analog (3.5 mm jack) : Yes TechniSat specific adapter set necessary (available at 0000/3649)

Ethernet 10/100 (RJ-45) : Yes

F socket : 1

DC IN : 1

DECODER

Video decoder : MPEG-2 MP@HL/ML, H.264/MPEG-4 AVC

Audio decoder : MPEG-1 & MPEG-2 Layer I, II, III

DECRYPTION SYSTEM

Conax : Yes

CI+ : Yes (v1.3)

DISPLAY

Freeze frame : Yes

SD : Yes

HD : Yes

1080p : Yes

1080i : Yes

720p : Yes

576p : Yes

576i : Yes

Type : 7 segment, 4 digits, white

HANDLING/COMFORT

Page memory : 1000

Teletext subtitles : Yes

Media Player : Yes

Clock : Yes

Sleep timer : Yes

Channel presets : 9999

Teletext : Yes

HOTEL MODE

Protected access to hotel mode : Yes

Customisable start screen : Yes

Lockable volume : Yes

Menu locking : Yes

Control panel lock : Yes

Integrated LED clock : Yes

Selectable start source : Yes

Selectable start channel : Yes

OTHER FEATURES

OSD languages : German, Danish, English, French, Greek, Italian, Dutch, Norwegian, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian

Regional channel selection : Yes

Internet radio : Yes

AMBIENT OPERATING CONDITIONS
Ambient temperature : 5 ... 35 °C
Humidity : 10 ... 75 %
LNB CONTROL
Vertical : 14 V
Horizontal : 18 V
Band switch : 22 kHz
Current consumption : 400 mA
DiSEqC : 1.0 / 1.2
TECHNISAT ADDED VALUE SERVICES
ISIPRO : Yes
TECHNIFAMILY : Yes
AUTOINSTALL : Yes
SFI : Yes
INTERNET/NETWORK
Internet speed test : Yes
CONNECTIONS
HDMI™ (out) : 1
USB : 1 (USB 2.0)
Common Interface Plus (CI+) : Yes

Smartcard reader : Yes
Digital electric audio output : Yes
audio/video output analog (3.5 mm jack) : Yes TechniSat specific adapter set necessary (available at 0000/3649)
Ethernet 10/100 (RJ-45) : Yes
F socket : 1
DC IN : 1
DECODER
Video decoder : MPEG-2 MP@HL/ML, H.264/MPEG-4 AVC
Audio decoder : MPEG-1 & MPEG-2 Layer I, II, III
DECRYPTION SYSTEM
Conax : Yes
CI+ : Yes (v1.3)
DISPLAY
Freeze frame : Yes
SD : Yes
HD : Yes
1080p : Yes
1080i : Yes
720p : Yes
576p : Yes
576i : Yes
Type : 7 segment, 4 digits, white
HANDLING/COMFORT

Multimedia streaming on home network (via UPnP, server)
Electronic program guide (EPG)
Page memory : 1000
Teletext subtitles : Yes
Media Player : Yes
Clock : Yes
Sleep timer : Yes
Channel presets : 9999
Teletext : Yes
HOTEL MODE
Protected access to hotel mode : Yes
Customisable start screen : Yes
Lockable volume : Yes
Menu locking : Yes
Control panel lock : Yes
Integrated LED clock : Yes
Selectable start source : Yes
Selectable start channel : Yes
OTHER FEATURES
OSD languages : German, Danish, English, French, Greek, Italian, Dutch, Norwegian, Polish, Portuguese, Russian, Swedish, Spanish, Czech, Turkish, Hungarian
Regional channel selection : Yes
Internet radio : Yes

POWER CONSUMPTION	SUPPORTED FORMATS & CODECS	TUNER
In operation : 4.8 W without LNB	Video-CODECS : MPEG-2, MPEG-4, H.264	Tuner type : DigitalSat
Standby : < 0,3 W	Video-Formats : M4V, MP4, MKV, MOV, MPG, TS, TS4, Xvid, M2TS, AVI, ASF	DVB-S tuner : 1
POWER SUPPLY	Picture-Formats : BMP, JPEG, GIF, PNG, TIFF	Single Cable Solution (SatCR) : SCR1 = EN50494, SCR2 = EN50607
Nominal voltage : 230 V	Audio-Formats : WAV, MP3, AAC, FLAC, MP2, OGG, DDAC3, AIFF	Satellite radio : Yes
Frequency : 50 Hz	TECHNISAT CONNECT	Internet radio : Yes
Mains adapter : external DC 12V/2A	Control : Yes	Reception on : HD-TV, SD-TV, DVB radio
STREAMING	SFI : Yes	TECHNIROUTER ready : Yes
Cloud store : Ja		TUNER - SAT
DLNA Client : Yes		Reception range : 950 ... 2150 MHz
		Viterbi rates : 1/2, 2/3, 3/4, 5/6, 7/8
		DVB-S : QPSK
		DVB-S : 2 ... 45
		DVB-S2 : 8PSK - QPSK
		DVB-S2 : 2 ... 45
		FEC : Viterbi and Reed-Solomon
		SCOPE OF DELIVERY
		TECHNISTAR S6, remote control with batteries, external mains adapter, HDMI cable, quick start guide EN/FR/NL/CZ



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.