

KOKA 99 HD Plus PVC wh250m Pullbox

Art. Number 151703



KOKA 99 HD - PVC white - 250m reel

TRIAX KOKA 99 HD PVC type is a premium cable for indoor installations. The wide frequency range allows transmission of digital signals in both Cable-tv networks, Satellite antenna systems and Terrestrial antenna installations.

This cable is designed with a center conductor of bare copper (Cu) which offers high performance even over long distances. Due to the gas injected foam, which is far superior to the chemical foam, the copper conductor carries the signals without great losses. High shielding Class A means less problems with disturbances from external electrical devices and thereby a clear tv-picture.

Technical Specifications

ORDER INFORMATION

EAN Number 5702661517037

CONSTRUCTION

Dielectric - dimension mm	4.57 ± 0.1 mm
Dielectric - material	Foam PE
1. Shield foil – material	Alu/PET/Alu bonded
1. Shield foil - overlap %	20 %
Inner conductor - dimension mm	1.02 ± 0.01 mm
Inner conductor - material	Cu
Jacket – dimension mm	6.9 ± 0.1 mm
Jacket - material	PVC
2. Shield braid - material	Alu
2. Shield braid - coverage %	77 %
3. Shield foil – material	Alu/PET

SHIELDING

Screening attenuation @ 1000-2000 MHz | dB ≥ 95 dB



Technical Specifications

Screening attenuation @ 2000-3000 MHz dB	≥ 95 dB
Screening attenuation @ 30-1000 MHz dB	≥ 105 dB

TRANSFER IMPEDANCE

Transfer Impedance @ 5-30 MHz mΩ/m	≤ 5 mΩ/m
--------------------------------------	----------

CHARACTERISTICS

LOSS

Attenuation (20°C/100mtr) @ 1000 MHz dB	20.3 dB
Attenuation (20°C/100mtr) @ 100 MHz dB	6.5 dB
Attenuation (20°C/100mtr) @ 1350 MHz dB	23.6 dB
Attenuation (20°C/100mtr) @ 1600 MHz dB	26.2 dB
Attenuation (20°C/100mtr) @ 1750 MHz dB	27.3 dB
Attenuation (20°C/100mtr) @ 200 MHz dB	9.0 dB
Attenuation (20°C/100mtr) @ 2150 MHz dB	30.8 dB
Attenuation (20°C/100mtr) @ 2400 MHz dB	32.5 dB
Attenuation (20°C/100mtr) @ 3000 MHz dB	36.5 dB
Attenuation (20°C/100mtr) @ 470 MHz dB	13.5 dB
Attenuation (20°C/100mtr) @ 50 MHz dB	4.6 dB
Attenuation (20°C/100mtr) @ 5 MHz dB	1.9 dB
Attenuation (20°C/100mtr) @ 800 MHz dB	18.3 dB
Attenuation (20°C/100mtr) @ 862 MHz dB	18.8 dB

RETURN LOSS

Structural return loss @ 1000-2000 MHz dB	> 18 dB
Structural return loss @ 2000-3000 MHz dB	> 16 dB
Structural return loss @ 470-1000 MHz dB	> 20 dB
Structural return loss @ 5-470 MHz dB	> 23 dB

ELECTRICAL

Capacity pF/m	53 ± 2 pF/m
Impedance Ω	75 ± 3 Ω
Inner DC resistance Ω/km	≤ 21.5 Ω/km
Outer DC resistance Ω/km	<15 Ω/km
Velocity ratio %	83 ± 1 %

OPERATIONAL

Application	Indoor
Notified Body	0051
DoP number	TR0009
Screening Efficiency	EN50117 (Class A)
Fire Class	EN 50575 (Eca)



Technical Specifications

Suitable for	F-compression connector EX 6-49 NT Plus F-compression connector EX 6-49/83 F-compression connector CX3 7.0 QM (Quick-mount) with o-ring, 50 pcs. box F-compression connector CX3 4.9 SC short, 100 pcs. box F-twist on connector SFC 070 F-twist on connector SFC 045 KOSWI 3 IEC coax plug, angled, male KOKWI 3 IEC coax plug, angled,
Suitable for	F-compression connector EX 6-49 NT Plus F-compression connector EX 6-49/83 F-compression connector CX3 7.0 QM (Quick-mount) with o-ring, 50 pcs. box F-compression connector CX3 4.9 SC short, 100 pcs. box F-twist on connector SFC 070 F-twist on connector SFC 045 KOSWI 3 IEC coax plug, angled, male KOKWI 3 IEC coax plug, angled,

MECHANICAL

Cable length m	250 m
Colour	White
Packaging Depth m	0.320 m
Packaging Height m	0.260 m
Total Weight kg	0.048 kg
Packaging Width m	0.320 m
Minimum bending radius - single/repeated mm	35/70 mm
Net Weight kg	0.044 kg
Tara Weight kg	0.004 kg
Packaging Volume m3	0.000 m3