TRIAX

connecting the future

UPM 1400 Combi meter

Art. Number 304579



Technical Specifications

ORDER INFORMATION	
EAN Number	5702663045798
CHARACTERISTICS	
Audio decoding	MPEG-2 layer I and II (Music cam), MPEG4, AAC, Dolby Digital (AC-3)
Video decoding	MPEG1, MPEG-2 MP@ML, H.264, VC1, DV, MPEG-4, H.265 (1080p@60fps)
FREQUENCY RANGE	
Measurement Range	Combo COFDM, QAM & QPSK
Measurement Range A	DVB-S/S2
Measurement Range B	DVB-T/T2
Measurement Range C	DVB-C
Measurement Range D	H.265/HEVC & MPEG4
Frequency range | MHz	50...2150 MHz
Measurement sensitivity VHF/UHF | dBµV	35...105 dBµV
Measurement sensitivity SAT | dBµV	35...95 dBµV
ELECTRICAL	
Impedance | Ω	75 Ω
OPERATIONAL	
Remote voltage - DVB-T/SAT	DVB-T 5V, 12-24V / DVB-S 13V,18V, LNB Test 12V-20V
Battery type	Li-Ion
AC Supply voltage | VAC	100-240 VAC
DC Operating voltage | VDC	15 VDC
PSU/adapter INFO	Included Euro Plug (CEE 7/17)

Technical Specifications

PSU/adapter Art number	304527
CONNECTORS	
Connector IN	F-female
Connector USB	1
Connector LAN	1
MECHANICAL	
Display	TFT 5 inch color
Dimensions product (H x D x W) | mm	145 x 220 x 50 mm
Packing QTY	1
Packaging Height | m	0.125 m
Packaging Width | m	0.282 m
Packaging Depth | m	0.185 m
Packaging Volume | m3	0.007 m3
Net Weight | kg	0.850 kg
Tara Weight | kg	0.050 kg
Total Weight | kg	0.900 kg